



HeusTractors

Stougjesdijk 153 3271 KB

Mijnsheerenland NL

info@heustractors.com

+31 (0) 186 61 2333

XCMG XE150E

Fitted as standard with:



- Cummins QSB4.5 diesel engine
- 90 kW (121 hp) power
- Stage V
- Liquid-cooled
- Hydraulic system with double piston pumps, output of 2 × 123.5 l/min
- Hydraulic quick coupler
- Maximum travel speed of 5.2 km/h
- Caterpillar tracks 500 mm wide
- Advanced slewing system with a speed of 11.3 rpm
- Hammer function for use with a hydraulic demolition hammer
- Proportional demolition and sorting function

€0.00

Specifications

DIMENSIONS

Cabin width	2490
Counterweight free space	944
Cradle base	3839
Ground clearance	470
Height to top of roof	3030
Max. Digging depth	5535
Max. Digging height	8650
Max. Tipping height	6185
Max. Vertical digging depth	4697
Max. excavation radius	8295
Min. forcing radius	2475
Overall length with bin	7924
Overall width	2490
Platform width	2476
Track width	1990
Width of tracks	500

ENGINE

Cooling	Liquid
Rated speed	2200

HYDRAULIC SYSTEM

Driving system pressure	340
Main pressure safety valve	340
Main pump output	123.5
Steering pressure	40
Swing system pressure	225

OTHER

Diesel tank	260
Engine oil capacity	11
Hydro tank	140

TECHNICAL SPECIFICATIONS

Arm digging force	73.4
Ground pressure	40
Max traction force	121
Max. Digging force	107
Rotation speed	11.3

WEIGHT

Own weight	14800
------------	-------

Pictures



