HeusTractors
Stougjesdijk 153 3271 KB
Mijnsheerenland NL
info@heustractors.com
+31 (0) 186 61 2333

XCMG XC916-E



Fitted as standard with:

- Yunnei diesel engine with an output of 36.8 kW
- Payload of 1,600 kg
- Bucket capacity of 0.7 m³
- Compact and manoeuvrable design
- Hydrostatic transmission
- Maximum breakout force of 40 kN
- Traction force of 39 kN for stability on rough terrain
- Ergonomic cab with panoramic view and comfortable controls
- Equipped with heating and air conditioning for optimum working comfort
- Hydraulic quick-hitch system for easy attachment changes
- Hydraulic brake system for reliable safety

€35,000.00

Specifications

DIMENSIONS

Bin capacity	0.7
Cradle base	2470
Height to top of roof	2550
Max. Tipping height	2400
Overall length with bin	5235
Overall width	1980
Steering angle	40
Tipping range	780
Turning circle	4460

ENGINE

Power in kW	36.8
Rated speed	1650

TECHNICAL SPECIFICATIONS

Max traction force	39
Max. Breakout force	40
Total cycle time	11

WEIGHT

Max. Lifting capacity	2100
Own weight	4560

Pictures












XCMG






F
N
R