



HeusTractors

Stougjesdijk 153 3271 KB

Mijnsheerenland NL

info@heustractors.com

+31 (0) 186 61 2333



XCMG XE155-ECR

Fitted as standard with:

- Cummins B4.5 diesel engine
- 90 kW (121 hp) power
- Stage V
- Liquid cooling with variable-speed fan
- Hydraulic system with double plunger pumps, output of 2 × 123.5 l/min
- Hydraulic quick coupler
- Caterpillar of 500 mm width
- Advanced slewing system with a speed of 11.3 rpm

€0.00

Specifications

DIMENSIONS

Cabin width	2490
Counterweight free space	944
Cradle base	3839
Ground clearance	476
Height to top of roof	3030
Max. Digging depth	5535
Max. Digging height	8650
Max. Tipping height	6185
Max. Vertical digging depth	4697
Max. excavation radius	8295
Min. forcing radius	2475
Overall length with bin	7924
Overall width	2490
Platform width	2476
Track width	1990
Width of tracks	500

ENGINE

Cooling	Liquid
Rated speed	2200

HYDRAULIC SYSTEM

Driving system pressure	350
Main pressure safety valve	33.4
Main pump output	123.5
Steering pressure	40
Swing system pressure	255

OTHER

Diesel tank	200
Engine oil capacity	11
Hydro tank	90

TECHNICAL SPECIFICATIONS

Arm digging force	73.4
Ground pressure	41.5
Max. Digging force	106.9
Rotation speed	11.3

WEIGHT

Own weight	16600
------------	-------

Pictures



