HeusTractors
Stougjesdijk 153 3271 KB
Mijnsheerenland NL
info@heustractors.com
+31 (0) 186 61 2333

XCMG XE45E



Fitted as standard with:

- Kubota Stage-V engine
- Hammer function
- Proportionally controlled demolition/sorting function
- Air conditioning
- Rubber tracks
- Dozer blade
- Heated cab with ROPS/TOPS and OPG certification (ISO 12117-2:2008 and ISO 10262:1998)
- High-quality 7" touchscreen display
- Rear view camera
- Sun hood
- Additional counterweight
- Cruise control for demolition hammer function ("one-key crushing cruise")
- Hydraulic system with variable pump (132 l/min)
- Adjustable auxiliary hydraulics (24 MPa)

€51,000.00

Specifications

DIMENSIONS

8 ft digging depth with flat floor	3210
Chassis width	1850
Counterweight free space	597
Cradle base	1800
Ground clearance	290.5
Height of dozer blade	392 mm
Height of tracks	513
Height to top of roof	2649
Max cutting depth of dozer blade	417
Max. Digging depth	3342
Max. Digging height	5479
Max. Tipping height	4052
Max. Vertical digging depth	2680
Max. excavation radius	5740
Maximum lifting height of dozer blade	513
Maximum reach at GRP	5585
Min. forcing radius	1215
Minimum unloading height	1378
Overall length with bin	5250
Overall width	1850
Tail swing radius	1215
Track length	2249
Track width	1500
Width of tracks	350
Width of upper structure	1758

ENGINE

Cooling	Water

HYDRAULIC SYSTEM

Driving system pressure	2200
Main pressure safety valve	240
Main pump output	132
Steering pressure	240
Swing system pressure	206

HYDRAULIC SYSTEM OTHER

Diesel tank	65
Hydro tank	36

TECHNICAL SPECIFICATIONS

Arm digging force	22
Ground pressure	34
Max traction force	42
Max. Digging force	37
Rotation speed	9

WEIGHT

Own weight	4800

Pictures






XE45E


XCMG
XE45E


XCMG
XE45E




XCMG




XE45E




XCMG


XCMG




XCMG
18:45
P7
P7
P

