HeusTractors
Stougjesdijk 153 3271 KB
Mijnsheerenland NL
info@heustractors.com
+31 (0) 186 61 2333

XCMG XE155-WECR



Fitted as standard with:

- Cummins QSB4.5 Stage V diesel engine
- Heated cabin with ROPS certification
- 7" colour display with multilingual interface
- Rear view camera
- 360° view camera (panoramic)
- Short tail design (compact swing radius)
- Load-sensing hydraulic system with variable pump
- Hydraulic quick coupler preparation (with pipes to end of boom)
- Two proportionally controllable auxiliary functions (AUX1 & AUX2)
- Adjustable hydraulic flow and pressure via display
- Joystick control with integrated function buttons
- Automatic idle control (auto-idle)
- Air-suspension seat with armrests and belt
- All-round LED work lights
- Dozer blade
- 10.00-20 tyres (double mounted)
- Boom lock (transport position)
- Hydraulic tank 150 L / Diesel tank 265 L

€0.00

Specifications

DIMENSIONS

8 ft digging depth with flat floor	4599
Boom length	4900
Chassis width	2490
Counterweight free space	580
Cradle base	2600
Ground clearance	350
Height of dozer blade	648 mm
Height to top of roof	3198
Max cutting depth of dozer blade	534
Max. Digging depth	4805
Max. Digging height	9776
Max. Tipping height	7268
Max. Vertical digging depth	4229
Max. excavation radius	8646
Maximum lifting height of dozer blade	1262
Maximum reach at GRP	8426
Min. forcing radius	2859
Minimum unloading height	7268
Overall length with bin	7792
Overall width	250
Tail swing radius	1750
Track width	1750
Width of upper structure	2510

ENGINE

Cooling	Water
Rated speed	2000

HYDRAULIC SYSTEM

Driving system pressure	343
Main pressure safety valve	343
Steering pressure	39
Swing system pressure	255

OTHER

Diesel tank	200
Engine oil capacity	14
Hydro tank	110

TECHNICAL SPECIFICATIONS

Arm digging force	80
Max traction force	83
Max. Digging force	100
Rotation speed	9

WEIGHT

Max. Lifting capacity (1 mtr)	8900
Own weight	17900

Pictures







