



HeusTractors

Stougjesdijk 153 3271 KB
Mijnsheerenland NL
info@heustractors.com
+31 (0) 186 61 2333



XCMG XE19E

Fitted as standard with

- Kubota Stage-V
- Extendable track system
- 2 travel speeds
- Extendable track system
- Dozer blade

€24,780.00

Specifications

DIMENSIONS

Cabin width	990
Counterweight free space	433.5
Cradle base	1230
Ground clearance	147.5
Height of tracks	345
Height to top of roof	2395
Max. Digging depth	2455
Max. Digging height	3420
Max. Tipping height	2550
Max. Vertical digging depth	1605
Max. excavation radius	4005
Min. forcing radius	1575
Overall length with bin	3550
Overall width	1300
Platform width	980
Width of tracks	230

ENGINE

Cooling	Liquid
Rated speed	2400

HYDRAULIC SYSTEM

Driving system pressure	210
Main pressure safety valve	250
Main pump output	50.6
Steering pressure	35
Swing system pressure	110

OTHER

Diesel tank	25
Engine oil capacity	5
Hydro tank	14.6

TECHNICAL SPECIFICATIONS

Arm digging force	9.3
Ground pressure	33
Max traction force	17.8
Max. Digging force	13.8
Rotation speed	10

WEIGHT

Own weight	1825
------------	------

Pictures



