HeusTractors
Stougjesdijk 153 3271 KB
Mijnsheerenland NL
info@heustractors.com
+31 (0) 186 61 2333

XCMG XC918-EV



Fitted as standard with:

- Fully electric and emission-free
- Payload of 1.8 tonnes
- Bucket capacity of 1 m³
- Machine weight of 6.7 tonnes
- Maximum unloading height of 2.67 metres
- Low-maintenance, long-life lithium-ion battery
- Compact design for optimum manoeuvrability
- Advanced control system for smooth and efficient operation
- Hydrostatic drive for precise control

€0.00

Specifications

DIMENSIONS

Bin capacity	1
Cradle base	2150
Height to top of roof	3405
Max. Tipping height	2670
Overall length with bin	5690
Overall width	2060
Steering angle	40
Tipping range	775
Turning circle	3700

ELECTRIC MOTOR

Battery capacity	100
Driving motor	40
Running time	6 - 8 uur

TECHNICAL SPECIFICATIONS	
Max traction force	26
Max. Breakout force	60.5
Total cycle time	9.7

WEIGHT	
Max. Lifting capacity	1798
Own weight	6700

Pictures
























XCMG




XCMG


ADVANCE


Low voltage: 14.1V
Drive motor speed
00000 r/Min
Hydraulic motor speed
00898 r/Min
D.M.Temp
012 ℃
H.M.Temp
015 ℃
0006.9A
330.4V
Hydraulic oil
6 ℃
Battery.Temp
010 ℃
40.4%
F N R
Power



