



HeusTractors

Stougjesdijk 153 3271 KB

Mijnsheerenland NL

info@heustractors.com

+31 (0) 186 61 2333

XCMG XC7-SR07E

Fitted as standard with:



- Electric drive with 80V LFP battery (35 kWh)
- 2 travel motors of 8.5 kW each + 15 kW working hydraulic motor
- Proportional hydraulic system with 3rd function (79 l/min, 21 MPa)
- Fully enclosed safety cabin
- Electrodynamic braking system + emergency stop button in cabin
- Standard 0.45 m³ bucket (1800 mm wide)
- Maximum tipping angle 101° and dumping range 550 mm
- Clearance height 1960 mm - working height up to 3800 mm
- Load capacity 910 kg - tipping load 1820 kg
- Swing circle over tyres: 1640 mm
- DC fast charging up to 16 kW (charging time ±2.2 hours)

€0.00

Specifications

DIMENSIONS

Bin capacity	0.45
Cradle base	1079
Ejection height	2400
Ground clearance	185
Height to top of roof	1960
Loading height	2400
Maximum angle on ground	32
Overall length with bin	3410
Overall length without bin	2703
Overall width	1640
Range (m)	550
Storage angle at max. height	40
Tilting angle at max. lifting height	101
Tipping angle	22
Total working height	3800
Track width	1370
Tray width	1800
Turning circle	1792

ELECTRIC MOTOR

Driving motor	8.5
Running time	6 - 8 uur

HYDRAULIC SYSTEM

Oil yield	79
Workload	210 bar

TECHNICAL SPECIFICATIONS

Max. Digging force	21.5
Total cycle time	11

WEIGHT

Own weight	3150
------------	------

Pictures







