



HeusTractors

Stougjesdijk 153 3271 KB

Mijnsheerenland NL

info@heustractors.com

+31 (0) 186 61 2333

XCMG XE27E-R

Fitted as standard with:



- Kubota D1105 diesel engine
- 15.4 kW (20.9 hp) power
- Stage V emission standard
- Zero-tail swing design
- Boom swing function
- Hydraulic operation
- Canopy design
- Swing speed 10 rpm
- Travel speed 2.0 - 3.1 km/h
- Joystick controls
- AUX1 & AUX2 hydraulic connections
- Maximum flow rate AUX1 & AUX2 25 L/min
- Traction control

€29,760.00

Specifications

DIMENSIONS

Counterweight free space	535
Cradle base	1980
Ground clearance	290
Height of tracks	457
Height to top of roof	2580
Max. Digging depth	2800
Max. Digging height	4390
Max. Tipping height	3120
Max. Vertical digging depth	2310
Max. excavation radius	4750
Min. forcing radius	1980
Overall length with bin	4190
Overall width	1500
Platform width	1350
Track width	1200
Width of tracks	300

ENGINE

Cooling	Liquid
Rated speed	2400

HYDRAULIC SYSTEM

Driving system pressure	243
Main pressure safety valve	243
Main pump output	82.8
Steering pressure	39
Swing system pressure	190

OTHER

Diesel tank	33
Engine oil capacity	5.1
Hydro tank	22

TECHNICAL SPECIFICATIONS

Arm digging force	14
Ground pressure	26.4
Max traction force	29.7
Max. Digging force	23
Rotation speed	10

WEIGHT

Own weight	2780
------------	------

Pictures



